

# LIFTING EQUIPMENT

## LEVER HOISTS

- Lightweight steel construction
- Short steel handle rotates 360° to allow operation in any position
- Load brake assures safety and load control
- High tensile alloy steel load chain for increased strength and durability
- Latched swivel hooks for added security
- Enclosed chain guide ensures dirt and dust do not affect operation
- Meets ASME B30.16

KLETON

Model No.	Lift'	Cap. lbs.	Wt. lbs.	Price/Each
LW562	5	1500	15	
LW563	5	2000	18	
LW564	5	3000	24	
LW565	5	6000	42	
LS550	5	12 000	62	



## CHAIN HOISTS

- Lightweight steel construction
- Triple spur geared for easy lifting
- Load brake assures safety and load control
- High tensile alloy steel load chain for increased strength and durability
- Latched swivel hooks for added security
- Enclosed chain guide ensures dirt and dust do not affect operation
- Meets ASME B30.16

KLETON

Model No.	Lift'	Cap. lbs.	Wt. lbs.	Price/Each
LS534	10	1000	24	
LS535	10	2000	29	
LW569	10	3000	44	
LW570	10	4000	48	
LS538	10	6000	59	
LS539	10	10 000	100	
LW573	20	1000	36	
LS541	20	2000	40	
LW575	20	3000	59	
LW576	20	4000	62	
LS544	20	6000	84	
LS545	20	10 000	136	



## ADJUSTABLE TROLLEYS

- Easily adjusts to fit various flanges, I-beams and H-beams
- Use on straight or curved track
- Can be installed or removed at any position on the beam
- Heavy-duty cast iron wheels
- Deep width flange provides superior contact with the beam
- Geared trolleys include two geared wheels operated by hand chain
- Safety plate included
- Meets ASME B30.16

KLETON

Model No.	Fits I beams"	Cap. lbs.	Wt. lbs.	Price /Each
<b>PLAIN</b>				
LS551	2 11/16 - 5 3/8	1000	10	
LS552	3 1/8 - 6 1/4	2000	17	
LW554	3 1/8 - 6 1/4	4000	28	
LS554	3 7/16 - 7 3/8	6000	46	
LS555	4 13/16 - 9 9/16	10 000	73	
<b>GEARED</b>				
LS556	2 11/16 - 5 1/4	1000	18	
LW558	3 1/8 - 5 15/16	2000	25	
LS558	3 1/8 - 7 1/16	4000	36	
LW560	3 7/16 - 7 3/8	6000	54	
LS560	4 3/4 - 7 3/4	10 000	81	

Adjustable Plain Trolley



Adjustable Geared Trolley